


## Datasheet for: 110402


**Push-in L-fitting, R 1/4 o., for hose exterior Ø 8 mm**

Push-in L-fitting, R 1/4 o., for hose exterior Ø 8 mm, Working pressure max. 15 bar, Stainless steel 1.4404 . For use with aggressive media and in areas susceptible to corrosive outside influences, in the food processing industry and in hygienic and sanitary applications.

Type number	52.014-8 ES
Article number	110402
EAN/barcode	 4047322268899
Your price	34,26 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

For tube O.D.	8 mm
L1	21.0 mm
L2	20.0 mm
Material	Stainless steel 1.4404
Max. medium temperature	150 °C
Max. operating temperature	150 °C
Max. working pressure	15 bar
Min. medium temperature	-20 °C
Min. operating temperature	-20 °C
Page No.	WEB
Standard thread	ISO 7-1
Suitable pipe materials	PVDF, PTFE, PA, PU
Thread	R 1/4
Working pressure pulsate	10.0 bar

## Variants

Article number	Thread	For tube O.D.	Price
110402	R 1/4	8 mm	34,26 € / Stk
110399	R 1/8	6 mm	26,13 € / Stk
110400	R 1/8	8 mm	32,46 € / Stk
110401	R 1/4	6 mm	27,38 € / Stk
110398	R 1/8	4 mm	26,47 € / Stk
110403	R 1/4	10 mm	49,87 € / Stk

## More Pictures

