


Datasheet for: 115955


5/2-way valve, Mechanically actuated, »M5«, Tappet, G 1/4

 5/2-way valve, Mechanically actuated, »M5«, Tappet, G 1/4,
 Operating pressure - 10 bar, Temperature range -20 °C to 70 °C . 5/2-way valves - Mechanically operated -

| | |
|----------------|--|
| Type number | 511.1101 |
| Article number | 115955 |
| EAN/barcode |  4047322309288 |
| Your price | 34,33 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|-------------------------|--|
| Connection | G 1/4 |
| Exhaust connection | G 1/8 |
| Flow rate | 550 l/min |
| Flow rate measurement | At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar |
| Function | 5/2 |
| Max. operating pressure | 10 bar |
| Max. temperature range | 70 °C |
| Min. temperature range | -20 °C |
| Page No. | HK451 |
| Page No. AS | AS077 |
| Symbol | 1 |
| Valve body | Aluminium alloy |

Variants

| <i>Article number</i> | <i>Connection</i> | <i>Flow rate</i> | <i>Price</i> |
|-----------------------|-------------------|------------------|---------------|
| 115955 | G 1/4 | 550 l/min | 34,33 € / Stk |
| 115954 | G 1/8 | 450 l/min | 34,33 € / Stk |

More Pictures

