


## Datasheet for: 116061


**5/2-way valve, Pneumatic, »4A«, bistable, G 1/8**

5/2-way valve, Pneumatic, »4A«, bistable, G 1/8, Operating pressure 1.5 - 8 bar, Temperature range max. 70 °C . 5/2-way pilot valves - Pneumatic -

Type number	516.5002
Article number	116061
EAN/barcode	 4047322309646
Your price	34,33 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Connection	G 1/8
Control air port	G 1/8
Exhaust connection	G 1/8
Flow rate	750 l/min
Flow rate measurement function	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Max. operating pressure	8 bar
Max. temperature range	70 °C
Min. operating pressure	1.5 bar
Operation	Bistable
Page No.	HK464
Page No. AS	AS084
Size	200
Symbol	28
Valve body	Aluminium alloy

## Variants

Article number	Connection	Exhaust connection	Flow rate	Size	Price
116061	G 1/8	G 1/8	750 l/min	200	34,33 € / Stk
116059	M5	M5	300 l/min	100	31,78 € / Stk
116064	G 3/8	G 1/4	1500 l/min	300	44,46 € / Stk
116063	G 1/4	G 1/4	1300 l/min	300	44,46 € / Stk
116065	G 1/2	G 1/2	2000 l/min	400	79,73 € / Stk
116060	G 1/8	G 1/8	500 l/min	100	31,78 € / Stk
116062	G 1/4	G 1/8	850 l/min	200	34,33 € / Stk

## More Pictures

