

Datasheet for: 107789



**GEKA threaded piece, 360° rotating, bright brass, G 1 exterior**

GEKA threaded piece, 360° rotating, bright brass, G 1 exterior, Operating pressure max. 40 bar, Medium/ambient temp. -10°C to 90°C . Claw couplings (claw distance: 40 mm) made of brass for water, industrial, mortar, suction and discharge hoses. Suitable for a wide range of applications, e.g. industrial plant engineering, civil and structural engineering, environmental engineering, manual trades, domestic water engineering, horticulture and landscaping, agriculture and forestry, etc. Available in a rigid or 360° swivelling version. The two systems can also be easily coupled to one another!

Type number	K 213 A
Article number	107789
EAN/barcode	 4047322133203
Your price	21,66 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Connection	G 1 ET
Max. ambient temperature	90 °C
Max. medium temperature	90 °C
Max. operating pressure	40 bar
Min. ambient temperature	-10 °C
Min. medium temperature	-10 °C
Page No.	HK608
Sealant	NBR

## Variants

<i>Article number</i>	<i>Connection</i>	<i>Price</i>
107789	G 1 ET	21,66 € / Stk
107787	G 1/2 ET	17,70 € / Stk
107788	G 3/4 ET	18,40 € / Stk