


Datasheet for: 107723

Hydraulic coupling, Series A, I.D. 13, Brass, G 1/2 IT


Hydraulic coupling, Series A, I.D. 13, Brass, G 1/2 IT, Operating pressure max. 250 bar, Operating temp. -30 °C to 100 °C . Acc. to ISO 7241-1, A Series. This coupling series combines an extremely small pressure drop with maximum hydraulic power transmission. Interchangeable with all couplings and plugs manufactured according to the above standard. The patented pressure eliminator permits disconnection even if back pressure has built up (up to 200 bar). The pressure eliminator can be used in all applications where there is a risk of pressure build-up after the line has been separated. It allows effortless connection under pressure. The mating part must be pressureless in order for the eliminator to function optimally. Areas of application: Agricultural machines, construction machines, municipal engineering, transportation engineering, industrial plant.

| | |
|----------------|--|
| Type number | 242.01 A |
| Article number | 107723 |
| EAN/barcode |  4047322056656 |
| Your price | 34,68 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|----------------------------|---------------------|
| Ball | Stainless steel |
| Connection | G 1/2 IT |
| Flow rate (oil) | 30 l/min |
| Housing | Brass |
| Length | 63.0 mm |
| Max. operating pressure | 250 bar |
| Max. operating temperature | 100 °C |
| Min. operating temperature | -30 °C |
| Page No. | HK605 |
| Page No. SK | SK088 |
| Sealant | NBR |
| Spring | Stainless steel |
| Unlocking sleeve | Nickel-plated brass |
| Valve | Hard drawn brass |
| a/f | 27 mm |

More Pictures

