


## Datasheet for: 110696


**Straight connector, for hose 10/8 mm, AF1 16,, AF2 14**

Straight connector, for hose 10/8 mm, AF1 16,, AF2 14, Pressure range max. 25 bar, Temp. -40 °C to 200 °C Stainless steel 1.4404 . Supplied without seals. For use with corrosive media and at high temperatures. Screw fitting series made of stainless steel for all applications where compliance with strict tightness, pressure and temperature requirements is essential. The parts are manufactured without rubber seals, in other words they are ideal for very high temperatures or for use with corrosive liquids, e.g. in cases when FPM is no longer suitable.

Type number	11.300-10 ESH
Article number	110696
EAN/barcode	 4047322269209
Your price	21,76 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

For hose	10/8 mm
L1	39.0 mm
Material	Stainless steel 1.4404
Max. temperature range	200 °C
Max. working pressure	25 bar
Min. temperature range	-40 °C
Page No.	HK736
Recommended hose	PTFE hose
Sealant	Pure metal
a/f 1	16.0 mm
a/f 2	14.0 mm

## Variants

Article number	For hose	a/f 1	a/f 2	Price
110696	10/8 mm	16.0 mm	14.0 mm	21,76 € / Stk
110694	6/4 mm	12.0 mm	10.0 mm	14,08 € / Stk
110695	8/6 mm	14.0 mm	12.0 mm	15,84 € / Stk

## More Pictures

