

Datasheet for: 107912


Tempered coupling DN 6, Taps 9 mm, Blocking valve, Sleeve 45°

Tempered coupling DN 6, Taps 9 mm, Blocking valve, Brass, Hose sleeve 45°, Operating pressure max. 15 bar, Temp. -20 °C to 160 °C . Compatible with HASCO Z 8 system. For temperature control applications involving hot or cold water or heat transfer oil, e.g. for cooling circuits on plastics processing machines. Optionally with free passage, one or both sides sealing. Female-threaded couplings and plugs with female-threaded PTFE seal.

Type number	270.02
Article number	107912
EAN/barcode	 4047322257978
Your price	16,54 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Ball	Stainless steel
Hose connection	9 mm
Hose stem type	45°
Length	42.5 mm
Material	Brass 2.0401
Max. ambient temperature	160 °C
Max. medium temperature	160 °C
Max. operating pressure	15 bar
Medium	Air, water, oil, vacuum
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	HK615
Retaining ring	Stainless steel
Sealant	FPM (PTFE coated)
Spring	Stainless steel

Variants

<i>Article number</i>	<i>Hose stem type</i>	<i>Price</i>
107912	45°	16,54 € / Stk
107911	straight	11,45 € / Stk
107913	90°	16,54 € / Stk