

Datasheet for: 107928


Tempered coupling DN 6, Exterior thread, Brass, G 1/4 90°

Tempered coupling DN 6, Exterior thread, Brass 2.0401, G 1/4 90°, Operating pressure max. 15 bar, Temp. -20 °C to 160 °C . Compatible with HASCO Z 8 system. For temperature control applications involving hot or cold water or heat transfer oil, e.g. for cooling circuits on plastics processing machines. Optionally with free passage, one or both sides sealing. Female-threaded couplings and plugs with female-threaded PTFE seal.

Type number	270.36
Article number	107928
EAN/barcode	 4047322258142
Your price	16,54 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Ball	Stainless steel
Connecting thread	G 1/4 90°
Length	47.0 mm
Material	Brass 2.0401
Max. ambient temperature	160 °C
Max. medium temperature	160 °C
Max. operating pressure	15 bar
Medium	Air, water, oil, vacuum
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	HK615
Retaining ring	Stainless steel
Sealant	FPM (PTFE coated)
Spring	Stainless steel
a/f	17 mm

Variants

<i>Article number</i>	<i>Connecting thread</i>	<i>Price</i>
107928	G 1/4 90°	16,54 € / Stk
107923	M14x1.5 straight	12,46 € / Stk
107924	G 1/4 straight	12,46 € / Stk
107927	M14x1.5 90°	16,54 € / Stk
107926	G 1/4 45°	16,54 € / Stk
107925	M14x1.5 45°	16,54 € / Stk