


Datasheet for: 106704


OR valve, 3 x G 1/4 Aluminium

OR valve, 3 x G 1/4, Operating pressure 2 - 10 bar, Temperature range -10 °C to 80 °C, Aluminium . The valve has two inlets and one outlet. A signal appears at the outlet when the left or right inlet is pressurised. If the pressure at the two inlets is different, the stronger of the two signals appears at the outlet.

Type number	ODER-14
Article number	106704
EAN/barcode	 4047322384209
Your price	16,58 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	43.0 mm
B	25.0 mm
Ball	Stainless steel
Flow rate at 6.3 bar and Δp 1.0 bar	1300 NI/min
Max. operating pressure	10 bar
Max. temperature range	80 °C
Min. operating pressure	2 bar
Min. temperature range	-10 °C
Page No.	HK486
Sealant	NBR
Thread	3 x G 1/4
Valve body	Aluminium

Variants

Article number	Thread	Flow rate at 6.3 bar and Δp 1.0 bar	Price
106704	3 x G 1/4	1300 NI/min	16,58 € / Stk
106703	3 x G 1/8	500 NI/min	15,77 € / Stk

More Pictures

