


## Datasheet for: 110441


**Straight push-in connector with plug nipple 6 mm, reducing**

Straight push-in connector with plug nipple 6 mm, reducing, for hose exterior Ø 4 mm, Working pressure max 15 bar, Stainless steel . For use with aggressive media and in areas susceptible to corrosive outside influences, in the food processing industry and in hygienic and sanitary applications.

Type number	59.0604 ES
Article number	110441
EAN/barcode	 4047322387385
Your price	22,11 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

For tube O.D.	4 mm
L1	31.0 mm
Material	Stainless steel 1.4404
Max. medium temperature	150 °C
Max. operating temperature	150 °C
Max. working pressure	15 bar
Min. medium temperature	-20 °C
Min. operating temperature	-20 °C
Page No.	WEB
Plug connection	6 mm
Suitable pipe materials	PVDF, PTFE, PA, PU
Working pressure pulsate	10.0 bar

## Variants

<i>Article number</i>	<i>For tube O.D.</i>	<i>Price</i>
110441	4 mm	22,11 € / Stk
110443	8 mm	30,10 € / Stk
110442	6 mm	28,53 € / Stk

## More Pictures

