

Plastic, with noise-reducing Star-Tip nozzle.

Ergonomic grip with a very high blowing force. Several possible hanging points thanks to the modified handle.

Robust yet lightweight for a long service life. With its ergonomic design, the gun can be used by both left and right-handed users!

| | |
|-------------------------|---|
| Material | POM |
| Tube | Nickel-plated brass |
| Connection thread | Rc 1/4 |
| Max. operating pressure | 16 bar (232 PSI) |
| Max. bursting pressure | 64 bar (928 PSI) |
| Temperature range | -20 °C to 60 °C |
| Airflow | 500 l/min (17,7 CFM) (Series 37) 190 l/min (6,7 CFM) (Series 38) |
| Noise level | 96 dB (Series 37), 79 dB (Series 38) |
| Thread | Nozzle side (male thread) M14x1 |



36 K/T

Blow gun, stepless adjustment, for use with extension tubes, without nozzle

| Art. No. | Type No. | Type of connection |
|----------|----------|---|
| 114390 | 36 A | Stem, I.D. 6 |
| 114391 | 36 B | Stem, I.D. 9 |
| 114392 | 36 C | Stem, I.D. 13 |
| 118433 | 36 K/T | Rc 1/4 IT |
| 114393 | 36 K | Push-in plug for DN 7.2 - 7.8 couplings |

Blow gun, stepless adjustment, 90 mm tube

| Art. No. | Type No. | Type of connection |
|----------|----------|---|
| 114394 | 37 A | Stem, I.D. 6 |
| 114395 | 37 B | Stem, I.D. 9 |
| 114396 | 37 C | Stem, I.D. 13 |
| 118465 | 37 V | Rc 1/4 IT |
| 114397 | 37 K | Push-in plug for DN 7.2 - 7.8 couplings |



37 K

Blow gun, stepless adjustment, with noise-reducing Star-Tip nozzle, 90 mm tube

| Art. No. | Type No. | Type of connection |
|----------|----------|---|
| 114398 | 38 A | Stem, I.D. 6 |
| 114399 | 38 B | Stem, I.D. 9 |
| 114400 | 38 C | Stem, I.D. 13 |
| 118485 | 38 V | Rc 1/4 IT |
| 114401 | 38 K | Push-in plug for DN 7.2 - 7.8 couplings |



38 A

Extension tube for basis blow guns

| Art. No. | Type No. | Designation |
|----------|----------|---|
| 114402 | 37.090 | Blow pipe with standard nozzle, 90 mm, bent |
| 114403 | 37.300 | Extension tube with standard nozzle, 300 mm, straight |
| 114404 | 37.500 | Extension tube with standard nozzle, 500 mm, straight |
| 114405 | 37.400 | Flexible extension tube with standard nozzle, 400 mm, bendable |
| 114406 | 38.090 | Blow pipe with Star-Tip nozzle, 90 mm, bent |
| 114407 | 38.300 | Extension tube with noise-reducing Star-Tip nozzle, 300 mm straight |
| 114408 | 38.500 | Extension tube with noise-reducing Star-Tip nozzle, 500 mm straight |




37.090



37.400



38.300 + 38.500



37.300 + 37.500



38.090

Department eDocumentation

Phone +49 7125 9497-41, -42, -53, -260, -330

Fax +49 7125 9497-99

 e-mail: eDocumentation@riegler.de

edition 12/2019

RIEGLER & Co. KG
www.riegler.net

Subject technical changes.

Accessories for plastic blow guns

| Art. No. | Type No. | Designation |
|----------|-----------|---|
| 114413 | 378.01 | Set of rubber-tip nozzles (Ø 14, 25, 35 mm) for sensitive surfaces fit directly onto the tube |
| 135938 | 378.01-14 | Rubber nozzle Ø 14 mm to plug onto the pipe |
| 135939 | 378.01-25 | Rubber nozzle Ø 25 mm to plug onto the pipe |
| 135940 | 378.01-35 | Rubber nozzle Ø 35 mm to plug onto the pipe |
| 114414 | 378.02 | Chip shield, (Ø 100 mm) fits directly onto the tube |
| 114415 | 378.03 | Silencer nozzle, fits directly onto the tube. Noise reducing |
| 114416 | 378.04 | Venturi nozzle for deflecting lightweight chips. Fits directly onto the tube |
| 114417 | 378.05 | Bypass nozzle reduces the output pressure to a safe value in case of back pressure. Fits directly onto the tube. |
| 114418 | 378.06 | Air curtain nozzle: Creates a protective air curtain that is suitable for deflecting lightweight wood chips or fluids. Fits directly onto the tube |
| 114419 | 378.07 | Silencer nozzle for reducing noise. Specially designed for use when space is limited. Fits directly onto the thread of the blow gun body (only for blow guns series 40) |
| 114389 | MH-41 | Magnet holder (for air and fluid gun and plastic blow guns) |



378.01



378.01-14



378.01-25



378.01-35



378.02



378.03



378.04



378.05



378.06



378.07



MH-41