

## Datasheet for: 103916


**Mini bleeder valve, 1.4305, G 1/8, Trigger pressure 1 - 4 bar**

Mini bleeder valve, Stainless steel, not component checked, Operating temp. -20 °C to 180 °C, G 1/8, Trigger pressure 1 - 4 bar . Manual adjustment of the blow-off pressure (lock nut). For compressed air and non-toxic, non-flammable gases, cannot be used for liquids due to free blow-off, not suitable for steam.

|             |           |
|-------------|-----------|
| Type number | 218.11-ES |
|-------------|-----------|

|                |        |
|----------------|--------|
| Article number | 103916 |
|----------------|--------|

|             |  |
|-------------|--|
| EAN/barcode | <br>4047322210966 |
|-------------|--|



|            |               |
|------------|---------------|
| Your price | 22,13 € / Stk |
|------------|---------------|

**Minimum order quantity**

|                        |       |
|------------------------|-------|
| Price Unit             | 1     |
| Quantity Unit          | Stk   |
| Packaging Unit         | 1     |
| Content                | 1 Stk |
| Minimum order quantity | 1     |

**Productdata**

|                            |                        |
|----------------------------|------------------------|
| C                          | 27.0 mm                |
| D                          | 7.0 mm                 |
| Material                   | Stainless steel 1.4305 |
| Max. operating pressure    | 60 bar                 |
| Max. operating temperature | 180 °C                 |
| Max. set pressure          | 4.0 bar                |
| Min. operating pressure    | 0.5 bar                |
| Min. operating temperature | -20 °C                 |
| Min. set pressure          | 1.0 bar                |
| Page No.                   | HK361                  |
| Sealant                    | FKM                    |
| Spring                     | Stainless steel 1.4310 |
| Thread                     | G 1/8                  |
| a/f                        | 16 mm                  |
| blow-off rate              | to 200 l/min           |
| do                         | 3.0 mm                 |

## Variants

| Article number | Min. set pressure | Max. set pressure | blow-off rate | Price         |
|----------------|-------------------|-------------------|---------------|---------------|
| 103916         | 1.0 bar           | 4.0 bar           | to 200 l/min  | 22,13 € / Stk |
| 103915         | 0.5 bar           | 1.0 bar           | to 50 l/min   | 22,13 € / Stk |
| 103917         | 3.0 bar           | 7.0 bar           | to 350 l/min  | 22,13 € / Stk |
| 103918         | 6.0 bar           | 12.0 bar          | to 650 l/min  | 22,13 € / Stk |
| 103919         | 10.0 bar          | 18.0 bar          | to 870 l/min  | 22,13 € / Stk |
| 103920         | 16.0 bar          | 32.0 bar          | to 1600 l/min | 22,13 € / Stk |
| 103921         | 30.0 bar          | 60.0 bar          | to 3000 l/min | 22,13 € / Stk |

## More Pictures

