


## Datasheet for: 136336


**3-way ball valve, nickel-plated brass, T-hole, Rp 1/2**

3-way ball valve, nickel-plated brass, Connection bottom, T-hole, Rp 1/2, DN 15, Operating temp. -15 °C to 120 °C, PN max. 25 bar . 3-way ball valve with full throughput, integrated ISO flange plate (ISO 5211) and double-sided sealed ball. Pressurisation is only possible via the lower connection.

Type number	1086 C
Article number	136336
EAN/barcode	 4047322504218
Your price	34,76 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	115.0 mm
B	62.0 mm
Ball	Nickel-plated brass (CW617N)
Ball seal	PTFE
DN	15.0
E	15.0 mm
H1	31.0 mm
H2	33.5 mm
Hand lever	Steel with plastic coating
Housing	Nickel-plated brass (CW617N)
L	64.0 mm
Max. operating temperature	120 °C
Min. operating temperature	-15 °C
PN	25 bar
Page No.	HK296
Standard thread	Rp thread acc. to ISO 7-1
Stem seal	PTFE / FKM
Thread	Rp 1/2
Thread material	Brass
a/f	27 mm

## Variants

Article number	Thread	DN	PN	a/f	Price
136336	Rp 1/2	15.0	25 bar	27 mm	34,76 € / Stk
136340	Rp 1 1/2	40.0	10 bar	55 mm	129,52 € / Stk
136337	Rp 3/4	20.0	16 bar	32 mm	48,44 € / Stk
136339	Rp 1 1/4	32.0	10 bar	50 mm	97,30 € / Stk
136341	Rp 2	50.0	10 bar	70 mm	210,31 € / Stk
136335	Rp 3/8	10.0	25 bar	22 mm	30,18 € / Stk
136334	Rp 1/4	8.0	25 bar	22 mm	30,18 € / Stk
136338	Rp 1	25.0	16 bar	41 mm	61,96 € / Stk

## More Pictures

