

Datasheet for: 103921


Mini bleeder valve, 1.4305, G 1/8, Trigger pressure 30 - 60 bar

Mini bleeder valve, Stainless steel, not component checked, Operating temp. -20 °C to 180 °C, G 1/8, Trigger pressure 30 - 60 bar . Manual adjustment of the blow-off pressure (lock nut). For compressed air and non-toxic, non-flammable gases, cannot be used for liquids due to free blow-off, not suitable for steam.

Type number	218.16-ES
-------------	-----------

Article number	103921
----------------	--------

EAN/barcode	 4047322211017
-------------	--

Your price	22,13 € / Stk
------------	---------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

C	27.0 mm
D	7.0 mm
Material	Stainless steel 1.4305
Max. operating pressure	60 bar
Max. operating temperature	180 °C
Max. set pressure	60.0 bar
Min. operating pressure	0.5 bar
Min. operating temperature	-20 °C
Min. set pressure	30.0 bar
Page No.	HK361
Sealant	FKM
Spring	Stainless steel 1.4310
Thread	G 1/8
a/f	16 mm
blow-off rate	to 3000 l/min
do	3.0 mm

Variants

Article number	Min. set pressure	Max. set pressure	blow-off rate	Price
103921	30.0 bar	60.0 bar	to 3000 l/min	22,13 € / Stk
103915	0.5 bar	1.0 bar	to 50 l/min	22,13 € / Stk
103916	1.0 bar	4.0 bar	to 200 l/min	22,13 € / Stk
103917	3.0 bar	7.0 bar	to 350 l/min	22,13 € / Stk
103918	6.0 bar	12.0 bar	to 650 l/min	22,13 € / Stk
103919	10.0 bar	18.0 bar	to 870 l/min	22,13 € / Stk
103920	16.0 bar	32.0 bar	to 1600 l/min	22,13 € / Stk

More Pictures

