

## Datasheet for: 106888


**Throttle check valve, Supply air throttle, quick conn. Hose 10/8, G3/8**

Throttle check valve, Supply air throttle (»V«) quick connector Hose 10/8, G 3/8 PN max. 10 bar, Temperature °C to 70 °C . For fine regulation of a cylinder piston speed in the forward and return motion and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder to restrict the incoming air. Compact type of construction, also ideal where space is restricted.

Type number	357.038-10
Article number	106888
EAN/barcode	 4047322181822
Your price	16,89 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Adjusting screw	Nickel-plated brass
B	50.0 mm
C	30.5 mm
Captive seals	Polyamide (glass fibre-reinforced)
For hose	10 / 8 mm
Hollow bolt	Nickel-plated brass
Internal parts	Brass with a bare metal surface
Max. operating pressure	10 bar
Max. temperature range	70 °C
Page No.	HK498
Pivoting arm	Nickel-plated brass
Sealant	NBR
Thread	G 3/8
a/f	20 mm

## Variants

Article number	Thread	For hose	a/f	Price
106888	G 3/8	10 / 8 mm	20 mm	16,89 € / Stk
106879	M5	4 / 2.5 mm	8 mm	9,72 € / Stk
106880	M5	5 / 3 mm	8 mm	9,72 € / Stk
106881	M5	6 / 4 mm	8 mm	9,72 € / Stk
106882	G 1/8	5 / 3 mm	14 mm	9,72 € / Stk
106883	G 1/8	6 / 4 mm	14 mm	9,72 € / Stk
106884	G 1/8	8 / 6 mm	14 mm	9,72 € / Stk
106885	G 1/4	6 / 4 mm	17 mm	10,02 € / Stk
106886	G 1/4	8 / 6 mm	17 mm	10,02 € / Stk
106887	G 1/4	10 / 8 mm	17 mm	10,54 € / Stk

## More Pictures

