

Datasheet for: 106933


Throttle check valve, Discharge throttle (»C«) quick connector

Throttle check valve, Discharge throttle (»C«) quick connector Hose 10/8, G 3/8, PN max. 10 bar, Temperature °C to 70 °C . For fine regulation of a cylinder piston speed and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder. Compact type of construction, also ideal where space is restricted.

| | |
|----------------|--|
| Type number | 358.038-10 |
| Article number | 106933 |
| EAN/barcode |  4047322181013 |
| Your price | 16,89 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|-------------------------|------------------------------------|
| Adjusting screw | Nickel-plated brass |
| B | 50.0 mm |
| C | 30.5 mm |
| Captive seals | Polyamide (glass fibre-reinforced) |
| For hose | 10 / 8 mm |
| Hollow bolt | Nickel-plated brass |
| Internal parts | Brass with a bare metal surface |
| Max. operating pressure | 10 bar |
| Max. temperature range | 70 °C |
| Page No. | HK500 |
| Pivoting arm | Nickel-plated brass |
| Sealant | NBR |
| Thread | G 3/8 |
| a/f | 20 mm |

Variants

| Article number | Thread | For hose | a/f | Price |
|----------------|--------|------------|-------|---------------|
| 106933 | G 3/8 | 10 / 8 mm | 20 mm | 16,89 € / Stk |
| 106924 | M5 | 4 / 2.5 mm | 8 mm | 9,47 € / Stk |
| 106925 | M5 | 5 / 3 mm | 8 mm | 9,47 € / Stk |
| 106926 | M5 | 6 / 4 mm | 8 mm | 9,47 € / Stk |
| 106927 | G 1/8 | 5 / 3 mm | 14 mm | 9,47 € / Stk |
| 106928 | G 1/8 | 6 / 4 mm | 14 mm | 9,47 € / Stk |
| 106929 | G 1/8 | 8 / 6 mm | 14 mm | 9,47 € / Stk |
| 106930 | G 1/4 | 6 / 4 mm | 17 mm | 10,08 € / Stk |
| 106931 | G 1/4 | 8 / 6 mm | 17 mm | 10,08 € / Stk |
| 106932 | G 1/4 | 10 / 8 mm | 17 mm | 10,60 € / Stk |

More Pictures

