

Datasheet for: 107721

Closing nipple locking on both sides, POM, G 1/2 IT, I.D. 11


Closing nipple locking on both sides, POM, G 1/2 IT, I.D. 11, Operating pressure max. 10 bar, Temp. -20 °C to 90 °C . Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series. Areas of application: manufacturing industry, chemical / pharmaceutical industry, food technology.

Type number	246.84
Article number	107721
EAN/barcode	 4047322061551
Your price	34,91 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Ball	Stainless steel
Connection	G 1/2 IT
DN	11
Flow rate (air)	1950 l/min
Flow rate measurement	at 6 bar and $\Delta p = 0.5$ bar
Housing	POM (Delrin), white
Length	48.0 mm
Max. ambient temperature	90 °C
Max. medium temperature	90 °C
Max. operating pressure	10 bar
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Operating pressure	Referred to medium temp. of 50 °C, static working pressure
Page No.	HK604
Page No. SK	SK087
Retaining ring	Stainless steel
Sealant	NBR
Sleeve	POM (Delrin), white
Spring	Stainless steel
Valve	Stainless steel 1.4305
a/f	27 mm

Variants

Article number	Connection	Flow rate (air)	DN	Max. operating pressure	a/f	Price
107721	G 1/2 IT	1950 l/min	11	10 bar	27 mm	34,91 € / Stk
107718	G 1/8 IT	440 l/min	4.3	15 bar	14 mm	21,69 € / Stk
107719	G 1/4 IT	840 l/min	6	15 bar	19 mm	21,02 € / Stk
107720	G 3/8 IT	1280 l/min	7.5	15 bar	22 mm	24,94 € / Stk
107722	G 3/4 IT	4500 l/min	13	10 bar	36 mm	41,33 € / Stk

More Pictures

