


Datasheet for: 107968


Tempered coupling DN 9, Exterior thread, Brass, G 1/2 straight

Tempered coupling DN 9, Exterior thread, Brass 2.0401, G 1/2 straight, Operating pressure max. 15 bar, Temp. -20 °C to 160 °C . Compatible with HASCO Z 8 system. For temperature control applications involving hot or cold water or heat transfer oil. Optionally with free passage, one or both sides sealing. Female-threaded couplings and plugs with female-threaded PTFE seal.

| | |
|----------------|--|
| Type number | 280.33 |
| Article number | 107968 |
| EAN/barcode |  4047322258906 |
| Your price | 16,89 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|--------------------------|-------------------------|
| Ball | Stainless steel |
| Connecting thread | G 1/2 straight |
| Length | 53.0 mm |
| Material | Brass 2.0401 |
| Max. ambient temperature | 160 °C |
| Max. medium temperature | 160 °C |
| Max. operating pressure | 15 bar |
| Medium | Air, water, oil, vacuum |
| Min. ambient temperature | -20 °C |
| Min. medium temperature | -20 °C |
| Page No. | HK617 |
| Retaining ring | Stainless steel |
| Sealant | FPM (PTFE coated) |
| Spring | Stainless steel |
| a/f | 21 mm |

Variants

| <i>Article number</i> | <i>Connecting thread</i> | <i>a/f</i> | <i>Price</i> |
|-----------------------|--------------------------|------------|---------------|
| 107968 | G 1/2 straight | 21 mm | 16,89 € / Stk |
| 107972 | M16x1.5 90° | 22 mm | 20,51 € / Stk |
| 107971 | G 3/8 90° | 22 mm | 20,51 € / Stk |
| 107969 | G 3/8 45° | 22 mm | 20,51 € / Stk |
| 107970 | M16x1.5 45° | 22 mm | 20,51 € / Stk |
| 107967 | G 3/8 straight | 22 mm | 15,15 € / Stk |
| 107966 | M16x1.5 straight | 22 mm | 21,12 € / Stk |