

Datasheet for: 101911


Standard pressure gauge, triangle front ring, G 1/8, -1 / bar

Standard pressure gauge, triangle front ring, Connection, rear, centric, G 1/8, Goods class 2.5, Measurement range -1 / bar, Ø40 . Bourdon-tube pressure gauge in standard design, either with panel-mounting bezel made of chrome-plated or black sheet steel or with 3-hole bezel made of chrome-plated sheet steel. Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

Type number	110.70
Article number	101911
EAN/barcode	 4047322015523
Your price	17,01 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Accuracy class	2.5
Connection	G 1/8
Connection position	rear, central
Diameter	40 mm
Front glass	Transparent plastic
Housing	Sheet steel
Lower / Upper range limit	Vacuum
Max. ambient temperature	60 °C
Max. medium temperature	60 °C
Measuring element	Copper alloy
Measuring range max. bar	0.0
Measuring range max. psi	0.0
Measuring range min. bar	-1.0
Measuring range min. psi	-14.5
Min. ambient temperature	-20 °C
Movement	Copper alloy

Page No. HK202
 Scale graduation in the bar area 0.05 bar
 Type 111.12

Variants

Article number	Measuring range min. bar	Measuring range max. bar	Measuring range min. psi	Measuring range max. psi	Diameter	Connection	Price
101911	-1.0	0.0	-14.5	0.0	40 mm	G 1/8	17,01 € / Stk
101912	0.0	1.0	0.0	14.5	40 mm	G 1/8	17,01 € / Stk
101913	0.0	1.6	0.0	23.0	40 mm	G 1/8	17,01 € / Stk
101914	0.0	2.5	0.0	36.0	40 mm	G 1/8	17,01 € / Stk
101915	0.0	4.0	0.0	58.0	40 mm	G 1/8	17,01 € / Stk
101916	0.0	6.0	0.0	86.0	40 mm	G 1/8	17,01 € / Stk
101917	0.0	10.0	0.0	145.0	40 mm	G 1/8	17,01 € / Stk
101918	0.0	16.0	0.0	230.0	40 mm	G 1/8	17,01 € / Stk
101919	0.0	25.0	0.0	360.0	40 mm	G 1/8	17,01 € / Stk
101920	-1.0	0.0	-14.5	0.0	50 mm	G 1/4	17,01 € / Stk
101921	0.0	1.0	0.0	14.5	50 mm	G 1/4	17,01 € / Stk
101922	0.0	1.6	0.0	23.0	50 mm	G 1/4	17,01 € / Stk
101923	0.0	2.5	0.0	36.0	50 mm	G 1/4	17,01 € / Stk
101924	0.0	4.0	0.0	58.0	50 mm	G 1/4	17,01 € / Stk
101925	0.0	6.0	0.0	86.0	50 mm	G 1/4	17,01 € / Stk
101926	0.0	10.0	0.0	145.0	50 mm	G 1/4	17,01 € / Stk
101927	0.0	16.0	0.0	230.0	50 mm	G 1/4	17,01 € / Stk
101928	0.0	25.0	0.0	360.0	50 mm	G 1/4	17,01 € / Stk
101929	-1.0	0.0	-14.5	0.0	63 mm	G 1/4	17,24 € / Stk
101930	0.0	1.0	0.0	14.5	63 mm	G 1/4	17,24 € / Stk
101931	0.0	1.6	0.0	23.0	63 mm	G 1/4	17,24 € / Stk
101932	0.0	2.5	0.0	36.0	63 mm	G 1/4	17,24 € / Stk
101933	0.0	4.0	0.0	58.0	63 mm	G 1/4	17,24 € / Stk
101934	0.0	6.0	0.0	86.0	63 mm	G 1/4	17,24 € / Stk
101935	0.0	10.0	0.0	145.0	63 mm	G 1/4	17,24 € / Stk
101936	0.0	16.0	0.0	230.0	63 mm	G 1/4	17,24 € / Stk
101937	0.0	25.0	0.0	360.0	63 mm	G 1/4	17,24 € / Stk

Variants

Article number	Measuring range min. bar	Measuring range max. bar	Measuring range min. psi	Measuring range max. psi	Diameter	Connection	Price
101938	0.0	40.0	0.0	580.0	63 mm	G 1/4	17,24 € / Stk
101939	0.0	60.0	0.0	860.0	63 mm	G 1/4	17,24 € / Stk
101940	0.0	100.0	0.0	1450.0	63 mm	G 1/4	17,24 € / Stk
101941	0.0	160.0	0.0	2300.0	63 mm	G 1/4	17,24 € / Stk
101942	0.0	250.0	0.0	3600.0	63 mm	G 1/4	17,24 € / Stk
101943	0.0	400.0	0.0	5800.0	63 mm	G 1/4	17,24 € / Stk