


## Datasheet for: 101527


**Mini mist oiler, G 1/4, Operating pressure 2 - 15 bar**

Mini mist oiler, G 1/4, Operating pressure 2 - 15 bar, Medium / ambient temp. max. 50 °C, Oil container made of polycarbonate . For mounting on pneumatic impact tools (nail drivers, tackers, screwdrivers) which work intermittently. Also suitable for tools with continuous compressed air demand (grinding and polishing machines). Fixed drip rate: Approx. 0.4 cm<sup>3</sup> per 100 work cycles, one filling = 3000 work cycles. Oil consumption in continuous operation (at 6 bar): 0.15 cm<sup>3</sup> / Nm<sup>3</sup> (varies depending on ambient temperature and oil used).

Type number	768 K
Article number	101527
EAN/barcode	 4047322117845
Your price	22,38 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	33.0 mm
B	60.0 mm
DN	8.0
Flow direction	any
Max. ambient temperature	50 °C
Max. medium temperature	50 °C
Max. operating pressure	15~15.0 bar
Min. operating pressure	2~2.0 bar
Mounting position	Oil intake at the lowest point
Oil bowl	Polycarbonate
Oil grade	CL 32 acc. to DIN 51517-ISO VG 32
Page No.	HK179
Thread	G 1/4

## Variants

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
101527	G 1/4	22,38 € / Stk
101528	G 3/8	22,38 € / Stk

## More Pictures

