

Datasheet for: 100206



Mist oiler »FUTURA«, PC container, Protective cage, Size 1, G 1/4

Mist oiler »FUTURA« with PC container and protective cage, Size 1, G 1/4, Input pressure max. 16 bar, Temp. -10 °C to 50 °C. Oil-mist lubricators with excellent flow rates in modern design. These devices can be used to top up oil automatically. A hose must be connected to the threaded nipple on the oil bowl for this purpose. When the oil filling button on the top of the device is pressed, a Venturi nozzle opens and sucks oil into the bowl under vacuum.

Type number	FU 901
Article number	100206
EAN/barcode	 4047322191791
Your price	35,07 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	52.0 mm
B	186.0 mm
Bowl	Polycarbonate container with protective cage
C	64.0 mm
Connecting thread	Material: Die-cast zinc
Flow rate	2750 l/min
Flow rate measurement	At $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	PA66 GF60
Max. input pressure	16 bar
Max. temperature range	50 °C
Medium	Compressed air, neutral gases
Min. temperature range	-10 °C
Oil grade	CL 32 acc. to DIN 51517-ISO VG 32
Page No.	HK042
Page No. SF	SF013
Sealant	NBR
Series	FUTURA
Sight dome	PC
Size	1
Thread	G 1/4

Variants

Article number	Thread	Flow rate	Size	Price
100206	G 1/4	2750 l/min	1	35,07 € / Stk
100207	G 3/8	2750 l/min	1	35,07 € / Stk
100208	G 3/8	8000 l/min	2	54,34 € / Stk
100209	G 1/2	8000 l/min	2	54,34 € / Stk
100210	G 3/4	14000 l/min	4	122,40 € / Stk
100211	G 1	14000 l/min	4	122,40 € / Stk

More Pictures

