

Datasheet for: 107275



End distributor socket, G 1/2, 2 stand. Coupl. I.D. 7.2, max. 15 bar

End distributor socket, with 2 standard couplings I.D. 7.2, input G 1/2, Operat. pressure max. 15 bar, Ambient temp. -10°C to 50°C. 2 or 3-way distributor sockets made of high-strength glass fibre-reinforced plastic (PA6 GF 30) for a wide range of applications. Available with 2 or 3 pre-assembled, brass quick disconnect couplings and 2 inlet thread sizes for input and output threads (Not combinable). All distributor sockets have a durable brass threaded insert, whose shape secures it against rotation and against axial shift due to its shape. Drilling diagram dimensions are identical for all distributor sockets, so a simpler and more flexible exchange replacement. Caution: Note that the distributor sockets should not be installed in danger zones. Danger zones are, for example, transport routes, escape routes, etc.

Type number	EVDK12-2
Article number	107275
EAN/barcode	 4047322401630
Your price	35,08 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Coupling	2 x brass coupling
Height	59.0 mm
Housing	Glass fibre-reinforced plastic PA6 GF 30
Inlet thread	G 1/2
Max. operating pressure	15 bar
Max. temperature range	50 °C
Max. tightening torque brass thread	12 Nm
Max. tightening torque mounting holes	4 Nm
Min. temperature range	-10 °C
Page No.	HK536
Page No. SK	SK021
Page No. TS	TS007

Thread material
Width

Brass
120.0 mm

Variants

Article number	Inlet thread	Coupling	Price
107275	G 1/2	2 x brass coupling	35,08 € / Stk
107278	G 3/4	3 x brass coupling	60,89 € / Stk
107276	G 1/2	3 x brass coupling	45,19 € / Stk
107277	G 3/4	2 x brass coupling	51,77 € / Stk

More Pictures

