


Datasheet for: 110703


T screw-in fitting, R 1/8 o., for hose 8/6 mm, AF 14/10

T screw-in fitting, R 1/8 o., for hose 8/6 mm, AF 14/10, Pressure range max. 25 bar, Temp. -40 °C to 200 °C Stainless steel 1.4404 . Supplied without seals. For use with corrosive media and at high temperatures. Screw fitting series made of stainless steel for all applications where compliance with strict tightness, pressure and temperature requirements is essential. The parts are manufactured without rubber seals, in other words they are ideal for very high temperatures or for use with corrosive liquids, e.g. in cases when FPM is no longer suitable.

Type number	14.118-8 ESH
Article number	110703
EAN/barcode	 4047322269285
Your price	35,29 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

For hose	8/6 mm
L1	46.0 mm
L2	17.0 mm
Material	Stainless steel 1.4404
Max. temperature range	200 °C
Max. working pressure	25 bar
Min. temperature range	-40 °C
Page No.	HK736
Recommended hose	PTFE hose
Sealant	Pure metal
Thread	R 1/8
a/f 1	14.0 mm
a/f 2	10.0 mm

Variants

Article number	Thread	For hose	a/f 1	a/f 2	Price
110703	R 1/8	8/6 mm	14.0 mm	10.0 mm	35,29 € / Stk
110706	R 1/4	10/8 mm	16.0 mm	12.0 mm	45,90 € / Stk
110702	R 1/8	6/4 mm	12.0 mm	10.0 mm	32,86 € / Stk
110705	R 1/4	8/6 mm	14.0 mm	10.0 mm	35,29 € / Stk
110704	R 1/4	6/4 mm	12.0 mm	10.0 mm	32,86 € / Stk

More Pictures

