

Datasheet for: 110708


L screw-in fitting, R 1/8 o., for hose 8/6 mm, AF 14/10

L screw-in fitting, R 1/8 o., for hose 8/6 mm, AF 14/10, Pressure range max. 25 bar, Temp. -40 °C to 200 °C Stainless steel 1.4404 . Supplied without seals. For use with corrosive media and at high temperatures. Screw fitting series made of stainless steel for all applications where compliance with strict tightness, pressure and temperature requirements is essential. The parts are manufactured without rubber seals, in other words they are ideal for very high temperatures or for use with corrosive liquids, e.g. in cases when FPM is no longer suitable.

Type number	15.118-8 ESH
-------------	--------------

Article number	110708
----------------	--------

EAN/barcode	 4047322269339
-------------	--

Your price	35,29 € / Stk
------------	---------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

For hose	8/6 mm
L1	23.0 mm
L2	40.0 mm
Material	Stainless steel 1.4404
Max. temperature range	200 °C
Max. working pressure	25 bar
Min. temperature range	-40 °C
Page No.	HK737
Recommended hose	PTFE hose
Sealant	Pure metal
Thread	R 1/8
a/f 1	14.0 mm
a/f 2	10.0 mm

Variants

Article number	Thread	For hose	a/f 1	a/f 2	Price
110708	R 1/8	8/6 mm	14.0 mm	10.0 mm	35,29 € / Stk
110710	R 1/4	8/6 mm	14.0 mm	10.0 mm	35,29 € / Stk
110707	R 1/8	6/4 mm	12.0 mm	10.0 mm	32,86 € / Stk
110709	R 1/4	6/4 mm	12.0 mm	10.0 mm	32,86 € / Stk
110711	R 1/4	10/8 mm	16.0 mm	12.0 mm	45,90 € / Stk

More Pictures

