


## Datasheet for: 103515


**Ball valve, High pressure design, G interior thread, Steel, G 1/4**

Ball valve, High pressure design, G interior thread, Steel, Operating temperature -10 °C to 100 °C, G 1/4, DN 6, PN max. 500 bar . For liquid and lubricating media. Available versions: - For solderless tube fittings acc. to DIN 2353, lightweight series acc. to ISO 8434-1. - For solderless tube fittings acc. to DIN 2353, heavy-duty series acc. to ISO 8434-1. - With female pipe thread acc. to DIN ISO 228-1 (BSP).

Type number	392.22
Article number	103515
EAN/barcode	 4047322081979
Your price	22,48 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	76.0 mm
B	55.0 mm
Ball	Hard-chrome plated steel
Bore inball	Full bore
Control ball seal	POM
DN	6.0
Housing	Steel
L	69.0 mm
Max. operating pressure	500 bar
Max. operating temperature	100 °C
Min. operating temperature	-10 °C
Page No.	HK298
Selector shaft	Steel
Selector shaft seal	NBR
Thread	G 1/4

## Variants

Article number	Thread	Max. operating pressure	DN	Price
103515	G 1/4	500 bar	6.0	22,48 € / Stk
103514	G 1/8	500 bar	4.0	27,60 € / Stk
103516	G 3/8	500 bar	10.0	26,32 € / Stk
103517	G 1/2	500 bar	12.0	28,77 € / Stk
103518	G 5/8	420 bar	16.0	112,17 € / Stk
103519	G 3/4	420 bar	20.0	50,32 € / Stk
103520	G 1	420 bar	25.0	64,19 € / Stk

## More Pictures

