


Datasheet for: 103812



Throttle valve, in block shape, Anodised aluminium, G 1/2

Throttle valve, in block shape, Anodised aluminium, Operating temperature -10 °C to 70 °C, G 1/2, PN max. 10 bar . Straight-way valves with restricted flow in both directions.

| | |
|----------------|--|
| Type number | 225.56 |
| Article number | 103812 |
| EAN/barcode |  4047322040662 |
| Your price | 22,48 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|----------------------------|--------------------|
| A | 65.0 mm |
| C | 30.0 mm |
| E | 50.0 mm |
| Housing | Anodized aluminium |
| I | 29.0 mm |
| Internal parts | Brass |
| L | 6.5 mm |
| M | 33.0 mm |
| Max. operating pressure | 10 bar |
| Max. operating temperature | 70 °C |
| Min. operating temperature | -10 °C |
| Page No. | HK352 |
| Sealant | NBR |
| Thread | G 1/2 |
| Thread for panel mounting | M22x1.5 |
| a/f | 26 mm |

Variants

| Article number | Thread | a/f | Thread for panel mounting | Price |
|----------------|--------|-------|---------------------------|---------------|
| 103812 | G 1/2 | 26 mm | M22x1.5 | 22,48 € / Stk |
| 103809 | G 1/8 | 15 mm | M12x0.75 | 11,09 € / Stk |
| 103810 | G 1/4 | 22 mm | M18x1.5 | 12,81 € / Stk |
| 103811 | G 3/8 | 22 mm | M18x1.5 | 19,81 € / Stk |

More Pictures

