


## Datasheet for: 102891



**2/2-solenoid valve,NC,dir. operated,24V DC,8W,FKM,G1/8,PN0-9bar**

2/2-way solenoid valve brass, NC, directly operated, 24V DC, 8W, Medium temp. -10°C to 140°C, FKM, G 1/8, PN - 9bar . Economy series available in three different versions - Directly operated - Combined operation - Pilot-operated For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Type number	MV 1322 G
Article number	102891
EAN/barcode	 4047322158800
Your price	35,75 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	54.0 mm
B	40.0 mm
DN	2.5
Electrical connection	For connector socket Pg 9/Pg 11 acc. to ISO 4400
Function	normally closed (NC)
Housing	Brass
Internal parts	Stainless steel
Max. ambient temperature	80 °C
Max. medium temperature	140 °C
Max. operating pressure	9 bar
Min. ambient temperature	-10 °C
Min. medium temperature	-10 °C
Page No.	HK320
Protection IP	IP 65 (with connector socket fitted)
Sealant	FPM
Thread	G 1/8
Type	2
Valve seat	Brass

## Variants

Article number	Thread	Max. operating pressure	Max. ambient temperature	DN	Type	Price
102891	G 1/8	9 bar	80 °C	2.5	2	35,75 € / Stk
102890	G 1/8	8 bar	60 °C	2.3	1	31,34 € / Stk
102892	G 1/8	6 bar	80 °C	3.0	2	45,55 € / Stk
102893	G 1/4	9 bar	80 °C	2.5	2	45,55 € / Stk
102894	G 1/4	6 bar	80 °C	3.0	2	45,55 € / Stk
102895	G 1/4	2 bar	80 °C	4.5	2	45,55 € / Stk

## More Pictures

