

Datasheet for: 156009


Rem. double threaded nipple, con. sealing,R 2 o.,R 2 o.,Brass

Removable double threaded nipple, conical sealing, R 2 o., R 2 o., Brass, Max. working pressure 25 bar, Max. operating temp. 150°C . **As long as stock lasts. Subject to prior sale. Due to stock clearing, the items are excluded from return. The warranty obligation is not affected. Dimensions may vary slightly.**

Type number	MS252L22G
Article number	156009
EAN/barcode	 4047322623865
Your price	22,59 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 St
Minimum order quantity	1

Productdata

L1	85.0 mm
Material	Brass CW614N
Max. operating temperature	150 °C
Max. working pressure	25 bar
Page No.	WEB
Thread 1	R 2
Thread 2	R 2
a/f	80 mm

Variants

Article number	Thread 1	Thread 2	a/f	Price
156009	R 2	R 2	80 mm	22,59 € / Stk
156006	R 1/4	R 3/8	19 mm	0,91 € / Stk
156227	R 1	R 1	50 mm	5,40 € / Stk

Variants

<i>Article number</i>	<i>Thread 1</i>	<i>Thread 2</i>	<i>a/f</i>	<i>Price</i>
156008	R 1 1/2	R 1 1/2	70 mm	14,92 € / Stk
156226	R 3/4	R 3/4	36 mm	3,00 € / Stk
156004	R 1/8	R 1/8	15 mm	0,86 € / Stk
156007	R 1 1/4	R 1 1/4	60 mm	8,98 € / Stk