

## Datasheet for: 135125


**Push-in L-fitting, rotating, G 1/8 o., for hose exterior Ø 6 mm**

Push-in L-fitting, rotating, G 1/8 o., for hose exterior Ø 6 mm, Working pressure max. 20 bar, Stainless steel 1.4404 . For use in more aggressive environments and corrosive media.

Type number	843.018-6 ES
Article number	135125
EAN/barcode	 4047322493338
Your price	35,86 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

For tube O.D.	6 mm
L1	22.0 mm
L2	26.0 mm
Material	Stainless steel 1.4404
Max. medium temperature	150 °C
Max. operating temperature	150 °C
Max. working pressure	20 bar
Min. medium temperature	-20 °C
Min. operating temperature	-20 °C
Page No.	HK719
Standard thread	DIN EN ISO 228-1
Suitable pipe materials	PVDF, PTFE, PA, PU
Thread	G 1/8
Working pressure pulsate	10.0 bar
a/f	14 mm

## Variants

Article number	Thread	For tube O.D.	a/f	Price
135125	G 1/8	6 mm	14 mm	35,86 € / Stk
135132	G 3/8	8 mm	21 mm	58,13 € / Stk
135129	G 1/4	8 mm	17 mm	37,60 € / Stk
135138	G 1/2	14 mm	27 mm	128,97 € / Stk
135123	M5	4 mm	11 mm	35,64 € / Stk
135131	G 1/4	12 mm	19 mm	93,34 € / Stk
135127	G 1/4	4 mm	17 mm	47,23 € / Stk
135134	G 3/8	12 mm	21 mm	80,35 € / Stk
135137	G 1/2	12 mm	27 mm	108,07 € / Stk
135128	G 1/4	6 mm	17 mm	41,47 € / Stk
135126	G 1/8	8 mm	14 mm	43,55 € / Stk
135133	G 3/8	10 mm	21 mm	69,93 € / Stk
135136	G 1/2	10 mm	27 mm	84,77 € / Stk
135139	G 1/2	16 mm	27 mm	137,14 € / Stk
135130	G 1/4	10 mm	17 mm	58,68 € / Stk
135124	G 1/8	4 mm	14 mm	40,17 € / Stk
135135	G 3/8	14 mm	22 mm	117,76 € / Stk

## More Pictures

