


## Datasheet for: 103004


**Pressure switch standard design, galvanised steel, 10 - 70 bar**

Pressure switch standard design, galvanised steel, Ambient temp. -25 °C to 85 °C, G 1/4, Setting range 10 - 70 bar, NC contact . For liquid, non-corrosive and gaseous media. Easy to adjust, even under pressure. Can be integrated in any mounting position. Pressure adjustment by means of a hexagon-head screw.

Type number	DS 4026
Article number	103004
EAN/barcode	 4047322126274
Your price	22,71 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Adjustment range max.	70.0 bar
Adjustment range min.	10.0 bar
Applications	Air, hydraulic oil, oil emulsions, water
Electrical connection	Tab connectors 2 x 6.3 x 0.8
Function	NC
Material	Galvanised steel
Max. ambient temperature	85 °C
Min. ambient temperature	-25 °C
Page No.	HK334
Switching frequency	200/min
Switching voltage	42 V
Thread	G 1/4
Type of construction	Spring-loaded piston

## Variants

Article number	Thread	Adjustment range min.	Adjustment range max.	Function	Price
103004	G 1/4	10.0 bar	70.0 bar	NC	22,71 € / Stk
102993	G 1/8	0.5 bar	2.0 bar	NO	19,10 € / Stk
102994	G 1/8	1.0 bar	10.0 bar	NO	19,10 € / Stk
102995	G 1/8	10.0 bar	70.0 bar	NO	22,71 € / Stk
102996	G 1/4	0.5 bar	2.0 bar	NO	19,10 € / Stk
102997	G 1/4	1.0 bar	10.0 bar	NO	19,10 € / Stk
102998	G 1/4	10.0 bar	70.0 bar	NO	22,71 € / Stk
102999	G 1/8	0.5 bar	2.0 bar	NC	19,10 € / Stk
103000	G 1/8	1.0 bar	10.0 bar	NC	19,10 € / Stk
103001	G 1/8	10.0 bar	70.0 bar	NC	22,71 € / Stk
103002	G 1/4	0.5 bar	2.0 bar	NC	19,10 € / Stk
103003	G 1/4	1.0 bar	10.0 bar	NC	19,10 € / Stk

## More Pictures

