

Datasheet for: 135256


Straight push-in bulkhead connector, M14x1.0, Stainless steel

Straight push-in bulkhead connector, M14x1.0, for hose exterior Ø 6 mm, Working pressure max. 20 bar, Stainless steel 1.4404 . For use in more aggressive environments and corrosive media.

Type number	851.014-6 ES
-------------	--------------

Article number	135256
----------------	--------

EAN/barcode



4047322494618

Your price	35,86 € / Stk
------------	---------------

Minimum order quantity

Price Unit	1
------------	---

Quantity Unit	Stk
---------------	-----

Packaging Unit	1
----------------	---

Content	1 Stk
---------	-------

Minimum order quantity	1
------------------------	---

Productdata

For tube O.D.	6 mm
L1	35.0 mm
Material	Stainless steel 1.4404
Max. medium temperature	150 °C
Max. operating temperature	150 °C
Max. working pressure	20 bar
Min. medium temperature	-20 °C
Min. operating temperature	-20 °C
Page No.	HK723
Suitable pipe materials	PVDF, PTFE, PA, PU
Thread	M14x1.0
Working pressure pulsate	10.0 bar
a/f	19 mm

Variants

Article number	Thread	For tube O.D.	a/f	Price
135256	M14x1.0	6 mm	19 mm	35,86 € / Stk
135257	M16x1.0	8 mm	21 mm	44,02 € / Stk
135260	M24x1.5	14 mm	29 mm	125,75 € / Stk
135259	M22x1.5	12 mm	27 mm	82,81 € / Stk
135261	M26x1.5	16 mm	30 mm	138,33 € / Stk
135255	M11x0.75	4 mm	14 mm	32,98 € / Stk
135258	M18x1.0	10 mm	22 mm	51,16 € / Stk

More Pictures

