


Datasheet for: 107782


GEKA angled hose piece, 360° rotating, bright brass, I.D. 25

GEKA angled hose piece, 360° rotating, bright brass, I.D. 25, Operating pressure max. 40 bar, Medium/ambient temp. -10 °C to 90 °C. Claw couplings (claw distance: 40 mm) made of brass for water, industrial, mortar, suction and discharge hoses. Suitable for a wide range of applications, e.g. industrial plant engineering, civil and structural engineering, environmental engineering, manual trades, domestic water engineering, horticulture and landscaping, agriculture and forestry, etc. Available in a rigid or 360° swivelling version. The two systems can also be easily coupled to one another!

Type number	K 304
Article number	107782
EAN/barcode	 4047322133234
Your price	22,74 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	I.D. 25
Max. ambient temperature	90 °C
Max. medium temperature	90 °C
Max. operating pressure	40 bar
Min. ambient temperature	-10 °C
Min. medium temperature	-10 °C
Page No.	HK607
Sealant	NBR

Variants

<i>Article number</i>	<i>Connection</i>	<i>Price</i>
107782	I.D. 25	22,74 € / Stk
107780	I.D. 13	17,24 € / Stk
107781	I.D. 19	18,40 € / Stk
107783	I.D. 32	35,89 € / Stk