

Datasheet for: 115964


5/2-way valve, Manual lever actuation, »4H«, engaging, G 1/8

5/2-way valve, Manual lever actuation, »4H«, engaging, G 1/8, Operating pressure - 8 bar, Temperature range -20 °C to 70 °C . 5/2- and 5/3-way valves - Manually operated -

Type number 514.1000

Article number 115964

EAN/barcode



4047322311892

Your price 35,97 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/8
Exhaust connection	G 1/8
Flow rate	750 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	5/2
Max. operating pressure	8 bar
Max. temperature range	70 °C
Min. temperature range	-20 °C
Operation	Bistable
Page No.	HK460
Page No. AS	AS082
Size	200
Symbol	13
Valve body	Aluminium alloy

Variants

Article number	Connection	Exhaust connection	Flow rate	Size	Price
115964	G 1/8	G 1/8	750 l/min	200	35,97 € / Stk
115965	G 1/4	G 1/8	850 l/min	200	35,97 € / Stk
115966	G 1/4	G 1/4	1300 l/min	300	50,76 € / Stk
115967	G 3/8	G 1/4	1500 l/min	300	50,76 € / Stk

More Pictures

