


Datasheet for: 113167


**Fitting 330, IT/IT, Rp/Rp 2, NBR seal, black malleable cast iron**

Fitting 330, flat sealing, IT/IT, Rp/Rp 2, NBR seal, Operating temp. -20°C to 200°C, black malleable cast iron, Hot-dip galva. . Maximum temperature and maximum operating pressure should not occur at the same time! Acc. to DIN EN 10242 (formerly DIN 2950) The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water; they are also protected against rust. These malleable iron fittings are used in machine construction, exterior lines, cold water lines and heating lines.

Type number	TFV 330-20-D
Article number	113167
EAN/barcode	 4047322384025
Your price	17,27 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	200 °C
Min. temperature range	-20 °C
Page No.	HK863
Standard	acc. ISO 7-1
thread	Hot dip galvanised
Surface	Rp/Rp 2
Thread	

## Variants

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
113167	Rp/Rp 2	17,27 € / Stk
113164	Rp/Rp 1	6,07 € / Stk
113161	Rp/Rp 3/8	5,28 € / Stk
113165	Rp/Rp 1 1/4	8,99 € / Stk
113162	Rp/Rp 1/2	4,02 € / Stk
113160	Rp/Rp 1/4	8,48 € / Stk
113163	Rp/Rp 3/4	5,01 € / Stk
113166	Rp/Rp 1 1/2	10,74 € / Stk
113169	Rp/Rp 3	53,05 € / Stk
113168	Rp/Rp 2 1/2	34,54 € / Stk