


Datasheet for: 112613

End distributor, Input G 1/2, Connection 1 x G 1/2


End distributor, Input G 1/2, Connection 1 x G 1/2, operat.pressure (air/water) max. 15 bar, ambient temp. 1 °C to 50 °C. Made of plastic PA6 GF 30. End and through distributor sockets made of high strength, glass fibre reinforced plastic (PA6 GF 30) with large range of applications. Optionally 1 or up to 3 connection options as well as 2 thread sizes for internal and external threads (cannot be combined). For vertical carrying of media. Universal distributor socket with up to 5 connection options. Suitable for vertical and/or horizontal carrying of media or the secure connection (avoidance of existing components) of pressure reducer or maintenance device, for example. All distributor sockets have a durable brass threaded insert, whose shape secures it against rotation and against axial shift due to its shape. Suitable for media compressed air (ambient temperature -10 °C to 50 °C) or water (ambient temperature 1 °C to 50 °C). Drilling diagram dimensions are identical for all distributor sockets, so a simpler and more flexible exchange between end, through and universal distributor sockets is ensured. Caution: Note that the distributor sockets should not be installed in danger zones. Danger zones are, for example, transport routes, escape routes, etc.

| | |
|----------------|--|
| Type number | EVD12-1 |
| Article number | 112613 |
| EAN/barcode |  4047322401531 |
| Your price | 17,30 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|-------------------------------------|--|
| Connecting thread | 1 x G 1/2 |
| Housing | Glass fibre-reinforced plastic PA6 GF 30 |
| Inlet thread | G 1/2 |
| Max. operating pressure | 15 bar |
| Max. temperature range | 50 °C |
| Max. tightening torque brass thread | 12 Nm |

Max. tightening torque
 mounting holes
 Min. temperature range
 Page No.
 Page No. TS

4 Nm
 1 °C
 HK844
 TS010

Variants

| <i>Article number</i> | <i>Inlet thread</i> | <i>Connecting thread</i> | <i>Price</i> |
|-----------------------|---------------------|--------------------------|---------------|
| 112613 | G 1/2 | 1 x G 1/2 | 17,30 € / Stk |
| 112618 | G 3/4 | 3 x G 1/2 | 40,90 € / Stk |
| 112614 | G 1/2 | 2 x G 1/2 | 22,17 € / Stk |
| 112615 | G 1/2 | 3 x G 1/2 | 26,39 € / Stk |
| 112617 | G 3/4 | 2 x G 1/2 | 37,61 € / Stk |
| 112616 | G 3/4 | 1 x G 1/2 | 33,48 € / Stk |