


Datasheet for: 100764


Pressure regulator »Standard-mini«, Size 0, G 1/8, 0.15 - 7 bar

Pressure regulator »Standard-mini« incl. pressure gauge, Size 0, G 1/8, Input pressure max. 28 bar, Control range 0.15 - 7 bar . Reversible diaphragm pressure regulators with self-relieving design in compact design. The pressure setting can be locked by pushing the knob down.

Type number	480.12
Article number	100764
EAN/barcode	 4047322092111
Your price	23,43 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	43.0 mm
B	72.5 mm
C	9.5 mm
D	63.0 mm
DN	5.0
Flow rate	340 l/min
Flow rate measurement	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Die-cast zinc, painted silver
Max. ambient temperature	60 °C
Max. control range	7.0 bar
Max. input pressure	28 bar
Max. medium temperature	60 °C
Min. control range	0.15 bar
Page No.	HK114
Pressure gauge display max.	10.0 bar
Pressure gauge display min.	0.0 bar
Sealant	NBR/TPU

Series
 Spring bonnet
 Thread

Standard-mini
 POM-brass
 G 1/8

Variants

Article number	Thread	Min. control range	Max. control range	Price
100764	G 1/8	0.15 bar	7.0 bar	23,43 € / Stk
100763	G 1/8	0.1 bar	3.5 bar	23,43 € / Stk
100765	G 1/8	0.5 bar	10.0 bar	23,43 € / Stk
100766	G 1/4	0.1 bar	3.5 bar	23,43 € / Stk
100767	G 1/4	0.15 bar	7.0 bar	23,43 € / Stk
100768	G 1/4	0.5 bar	10.0 bar	23,43 € / Stk

More Pictures

