


Datasheet for: 130277


3/2-5/2-way valve NAMUR, G 1/4 (1), G 1/4 (3+5), 230 V, 50 Hz

3/2-5/2-way valve NAMUR, Alu, Temp. -5 °C to 50 °C, Working pressure 1.5-8 bar, Connection G 1/4 (1), G 1/4 (3 + 5), 230 V, 50 Hz . Pilot-operated 3/2 and 5/2-way spool valves with threaded ports and a NAMUR style interface. Combines high-quality design with a low price. By adding the conversion plate supplied with each valve, the device can be adapted to a 3/2-way function. The valve is turned on by a continuous signal. Turning off causes the piston to be returned to its initial position under pressure. Includes a manual operator as standard.

Type number	552.01
Article number	130277
EAN/barcode	 4047322456180
Your price	36,34 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

DN	8.0
Electrical connection	Connector socket PG 9 with LED display
Flow rate	1370 l/min
Housing	Aluminium
Manual control	latching/non-latching
Max. operating temperature	50 °C
Max. working pressure	8 bar
Medium	Air, neutral gases (filtered)
Min. operating temperature	-5 °C
Min. working pressure	1.5 bar
Page No.	HK309
Page No. AS	AS091
Port 1	G 1/4
Port 3	G 1/4
Port 5	G 1/4
Sealant	NBR
Voltage	230 V, 50 Hz

Variants

Article number	Voltage	Port 1	DN	Flow rate	Price
130277	230 V, 50 Hz	G 1/4	8.0	1370 l/min	36,34 € / Stk
130278	24 V DC	G 1/4	8.0	1370 l/min	36,34 € / Stk
103652	24 V DC	G 3/8	10.0	1650 l/min	48,57 € / Stk
103651	230 V, 50 Hz	G 3/8	10.0	1650 l/min	48,57 € / Stk
103650	24 V DC	G 1/4	8.0	1370 l/min	35,28 € / Stk
103649	230 V, 50 Hz	G 1/4	8.0	1370 l/min	35,28 € / Stk

More Pictures

