


Datasheet for: 115718


Ball valve »valve line«, Hand lever blue, IT/IT, G 2

Ball valve »valve line« Hand lever blue, Nickel-plated brass, IT/IT, G 2, DN 45, Operating temp. -20 °C to 120 °C, PN max 25 bar . Extremely economical standard ball valves made of nickel-plated brass for compressed air, water, non-toxic and non-corrosive gases and liquids.

Type number	334.09-E
Article number	115718
EAN/barcode	 4047322074292
Your price	36,62 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	160.0 mm
B	79.2 mm
Ball	Nickel-plated brass
Ball seal	PTFE
DN	45.0
Hand lever	Steel Q235-A (1.0038) with PVC-coating
Housing	Nickel-plated brass
L	99.0 mm
Max. operating pressure	25 bar
Max. operating temperature	120 °C
Min. operating temperature	-20 °C
Page No.	WEB
Page No. AS	AS052
Standard thread	G thread acc. to DIN EN ISO 288-1
Stem seal	NBR
Thread	G 2
Thread material	Nickel-plated brass

Variants

Article number	Thread	DN	Price
115718	G 2	45.0	36,62 € / Stk
115711	G 1/4	8.0	4,13 € / Stk
115712	G 3/8	10.0	4,13 € / Stk
115713	G 1/2	14.5	4,67 € / Stk
115714	G 3/4	19.0	6,57 € / Stk
115715	G 1	24.0	10,60 € / Stk
115716	G 1 1/4	30.0	16,87 € / Stk
115717	G 1 1/2	37.0	23,69 € / Stk

More Pictures

