


Datasheet for: 112520


Pre-assembly supports for stainless steel cutting ring fitting

Pre-assembly supports for stainless steel cutting ring fitting, M26x1.5, Pipe exterior Ø 18 mm, AF 22, PN max. 315 bar . When stainless steel pipes are assembled, they must always be pre-assembled in a hardened pre-assembly adapter. They must never be assembled directly in the stainless steel adapter. The cones of the pre-assembly adapters are susceptible to wear and must therefore be inspected at regular intervals to check that they are still true to gauge. We recommend using only seamless, soft-annealed, stainless steel pipes made of 1.4571 according to DIN 2391 Part 1 or DIN 2462, tolerance class D4/T3.

Type number	VMS 09
Article number	112520
EAN/barcode	 4047322169165
Your price	36,98 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

L1	45.0 mm
L2	15.0 mm
PN	315 bar
Page No.	HK839
Thread	M26x1.5
Tube O.D.	18 mm
a/f	22 mm

Variants

Article number	Tube O.D.	Thread	PN	a/f	Price
112520	18 mm	M26x1.5	315 bar	22 mm	36,98 € / Stk
112512	4 mm	M8x1.0	100 bar	10 mm	20,02 € / Stk

Variants

Article number	Tube O.D.	Thread	PN	a/f	Price
112513	6 mm	M10x1.0	100 bar	10 mm	20,02 € / Stk
112514	8 mm	M12x1.0	100 bar	12 mm	22,17 € / Stk
112515	6 mm	M12x1.5	315 bar	12 mm	24,78 € / Stk
112516	8 mm	M14x1.5	315 bar	12 mm	24,78 € / Stk
112517	10 mm	M16x1.5	315 bar	17 mm	26,35 € / Stk
112518	12 mm	M18x1.5	315 bar	17 mm	26,35 € / Stk
112519	15 mm	M22x1.5	315 bar	19 mm	30,09 € / Stk
112521	22 mm	M30x2.0	315 bar	24 mm	52,36 € / Stk

More Pictures

