

Datasheet for: 141610

Swing safety coupl. I.D. 5.5, ARO 210, Steel, Hose connec. 6.5x10


Swing safety coupling I.D. 5.5, ARO 210, Steel, Hose connection 6.5x10, Operating pressure max. 25 bar, Temp. -20 °C to 100 °C . Swing safety coupling with free passage. The plug-in nipple is inserted into the coupling body and rotated by an approx. 90° motion to make the connection. As soon as the "red ring" clicks into the intended slot then a secure connection has been made. To release the connection again, the "red ring" must be pulled out and the plug-in nipple is swivelled to the stopper into the starting position. Venting is done during uncoupling through a vent hole on the back side of the coupling. This coupling meets ISO standard DIN EN ISO 4414, EN 983. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, workshops, automotive.

Type number	420.32-SCH
-------------	------------

Article number	141610
----------------	--------

EAN/barcode	 4047322567367
-------------	---

Your price	24,05 € / Stk
------------	---------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	Hose connection 6.5x10
DN	5.5
Flow rate	820 l/min (air)
Flow rate measurement	at 6 bar and $\Delta_p = 0.5$ bar
Housing	Steel, QPQ treated
Length	63.0 mm
Max. temperature range	100 °C
Medium	Compressed air, gases
Min. temperature range	-20 °C
Operating pressure	max. 25 bar / max. 16 bar when attaching / detaching
Page No.	HK560
Page No. SK	SK043
Plug profile	acc. ARO 210
Sealant	NBR
Sleeve	Die-cast zinc, nickel-plated, red rubber coated

Threaded piece
a/f

Galvanised steel
20 mm

Variants

Article number	Connection	Length	Price
141610	Hose connection 6.5x10	63.0 mm	24,05 € / Stk
141611	Hose connection 8x12	66.0 mm	24,05 € / Stk

More Pictures

