

Datasheet for: 108119


Kamlok quick-connect socket with IT, D type, 1.4401, G 2


Kamlok quick-connect socket with interior thread, D type, Stainless steel 1.4401, G 2, for plug Ø 64 mm, Pressure max. 16 bar . High-quality, robust, universal coupling system with a safety clamp for quick and easy connection of two hoses or for joining one hose to a machine connection. A male part and a female part are joined together by shifting the handles. There is no need to turn the hose! Kamlok stainless steel couplings are designed for use with corrosive media in the chemical and petrochemical industries, steelmaking, shipbuilding, agriculture, etc. All female threaded couplings and connectors are with female thread sealing ring made of PTFE.

Type number	1114.20-ES
-------------	------------

Article number	108119
----------------	--------

EAN/barcode



4047322404532

Your price	37,06 € / Stk
------------	---------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	97.0 mm
C	71.0 mm
For plug Ø	64.0 mm
Max. operating pressure	16 bar
Max. temperature range	95 °C
Min. temperature range	-20 °C
Page No.	HK623
Sealant	NBR, resistant to oils and benzine
Thread	G 2

Variants

Article number	Thread	For plug Ø	Price
108119	G 2	64.0 mm	37,06 € / Stk
108117	G 1 1/4	46.0 mm	23,59 € / Stk
108120	G 2 1/2	76.5 mm	53,98 € / Stk
108118	G 1 1/2	54.0 mm	28,56 € / Stk
108122	G 4	120.0 mm	103,56 € / Stk
108121	G 3	92.0 mm	70,46 € / Stk
108116	G 1	37.0 mm	18,62 € / Stk
108115	G 3/4	32.0 mm	13,67 € / Stk

More Pictures

