


Datasheet for: 103506


Ball valve, High pressure design, Heavy-duty series, M16x1.5

Ball valve, High pressure design, Heavy-duty series, Steel, Operating temp. -10 °C to 100 °C, M16x1.5, DN 4, PN max. 500 bar . For liquid and lubricating media. Available versions:
 - For solderless tube fittings acc. to DIN 2353, lightweight series acc. to ISO 8434-1. - For solderless tube fittings acc. to DIN 2353, heavy-duty series acc. to ISO 8434-1. - With female pipe thread acc. to DIN ISO 228-1 (BSP).

Type number	392.11
Article number	103506
EAN/barcode	 4047322081863
Your price	24,11 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	76.0 mm
B	55.0 mm
Ball	Hard-chrome plated steel
Bore inball	Full bore
Control ball seal	POM
DN	4.0
For tube O.D.	8S mm
Housing	Steel
L	73.0 mm
Max. operating pressure	500 bar
Max. operating temperature	100 °C
Min. operating temperature	-10 °C
Page No.	HK298
Selector shaft	Steel
Selector shaft seal	NBR
Thread	M16x1.5

Variants

Article number	Thread	Max. operating pressure	DN	For tube O.D.	Price
103506	M16x1.5	500 bar	4.0	8S mm	24,11 € / Stk
103507	M18x1.5	500 bar	6.0	10S mm	25,52 € / Stk
103508	M20x1.5	500 bar	8.0	12S mm	26,32 € / Stk
103509	M22x1.5	500 bar	10.0	14S mm	27,73 € / Stk
103510	M24x1.5	500 bar	12.0	16S mm	30,52 € / Stk
103511	M30x2	420 bar	16.0	20S mm	49,51 € / Stk
103512	M36x2	420 bar	20.0	25S mm	57,55 € / Stk
103513	M42x2	420 bar	25.0	30S mm	74,31 € / Stk

More Pictures

