


Datasheet for: 107469


Quick-connect coupling I.D. 10, Robust design, Sleeve I.D. 10

Quick-connect coupling I.D. 10, galvanised steel / brass, Robust design, Sleeve I.D. 10, Operating pressure max. 16 bar . One-hand quick disconnect couplings, one side sealing, that combine optimal flow rates (approx. 4 times as high as the popular standard coupling DN 7.2) with minimal coupling forces. Suitable for all applications with an above-average air requirement and characterised by extreme conditions!

Type number	410.64
Article number	107469
EAN/barcode	 4047322273640
Your price	37,14 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	I.D. 10
DN	10
Flow rate	3900 l/min (air)
Flow rate measurement	at 6 bar and $\Delta_p = 0.5$ bar
Length	77.3 mm
Material	Nickel-plated steel, nickel-plated brass
Max. operating pressure	16 bar
Max. temperature range	100 °C
Min. temperature range	-20 °C
Page No.	WEB
Sealant	NBR
a/f	24 mm

Variants

<i>Article number</i>	<i>Connection</i>	<i>Length</i>	<i>Price</i>
107469	I.D. 10	77.3 mm	37,14 € / Stk
107470	I.D. 13	75.8 mm	36,41 € / Stk

More Pictures

