

Datasheet for: 141745

Swivel safety coupling I.D. 6, ISO 6150 C, Steel, Sleeve I.D. 10


Swivel safety coupling I.D. 6, ISO 6150 C, Steel, Sleeve I.D. 10, two-stage, Operating pressure max. 25 bar, Temp. -20°C to 100°C. High quality, robust and long lifetime one-hand rotation secure coupling. A secure connection is made by pushing in the plug-in nipple that clicks in audibly. Uncoupling is done by rotating the sleeve anti-clockwise. For this, the pending pressure in the coupling and line are vented, however the plug-in nipple is not completely released via a safety latch. The plug-in nipple can only be pulled out after a clockwise rotation of the sleeve. This coupling meets ISO standard DIN EN ISO 4414, EN 983. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, workshops, automotive, mining.

Type number	423.24-DREH
Article number	141745
EAN/barcode	 4047322566650
Your price	24,23 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	I.D. 10
DN	6
Flow rate	630 l/min (air)
Flow rate measurement	at 6 bar and $\Delta_p = 0.5$ bar
Housing	Steel, QPQ treated
Length	70.0 mm
Max. temperature range	100 °C
Medium	Compressed air, gases
Min. temperature range	-20 °C
Operating pressure	max. 25 bar / max. 16 bar when attaching / detaching
Page No.	HK569
Page No. SK	SK053
Plug profile	acc. ISO 6150 C
Sealant	NBR
Sleeve	Polyamide, red
Spring	Stainless steel

Threaded piece
 Valve
 a/f

Galvanised steel
 Polyphenylene sulfide (PPS)
 22 mm

Variants

<i>Article number</i>	<i>Connection</i>	<i>Price</i>
141745	I.D. 10	24,23 € / Stk
141746	I.D. 13	24,23 € / Stk
141744	I.D. 8	24,23 € / Stk
141743	I.D. 6	24,23 € / Stk

More Pictures

