


Datasheet for: 141554

Quick-connect coupl. I.D. 10, Steel/nickel-plated brass, R 1/2 ET



Quick-connect coupling I.D. 10, Steel / nickel-plated brass, R 1/2 ET, Operating pressure - 35 bar, Temp. -20 °C to 100 °C . Single-sided blocking and robust quick connect coupling with high flow performance. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling. These quick disconnect couplings are not suitable for direct attachment to pulsating tools. We recommend using our vibration dampers, according to ISO 6150 § 7.1. Areas of application: Pneumatic system, Machine and plant engineering, Measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, workshops, automotive, food technology, aerospace.

Type number	241.43-E
Article number	141554
EAN/barcode	 4047322568258
Your price	17,76 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	R 1/2 ET
DN	10
Flow rate	3500 l/min (air)
Flow rate measurement	at 6 bar and $\Delta_p = 0.5$ bar
Housing	Nickel-plated brass
Length	65.0 mm
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Operating pressure	- 35 bar
Page No.	HK553
Page No. SK	SK035
Sealant	NBR

Sleeve
 Spring
 Threaded piece
 Valve
 a/f

Galvanised steel
 Stainless steel
 Nickel-plated brass
 Nickel-plated brass
 24 mm

Variants

<i>Article number</i>	<i>Connection</i>	<i>a/f</i>	<i>Price</i>
141554	R 1/2 ET	24 mm	17,76 € / Stk
141553	R 3/8 ET	24 mm	17,76 € / Stk
141555	R 3/4 ET	27 mm	17,76 € / Stk

More Pictures

