


## Datasheet for: 106413


**3/2-way mini valve, manual, Palm button, NC, monostable 4 mm side**

3/2-way miniature valve, manual, Palm button, NC, monostable, 4 mm side, Operating pre. 0.5-10 bar, Operating temp. -10°C to 60°C . Monostable (non-latching) and bistable (latching) versions available.

Type number	512.603
Article number	106413
EAN/barcode	 4047322096430
Your price	37,40 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Connection	Plug-in connector Ø 4 mm on side
Flow rate at 6 bar and $\Delta p$ 0.5 bar	35 NI/min
Function	3/2 NC
Max. operating pressure	10 bar
Max. operating temperature	60 °C
Min. operating pressure	0.5 bar
Min. operating temperature	-10 °C
Nominal Ø	2.5 mm
Operating pressure at 6 bar	8 N
Operation	Monostable
Page No.	HK452
Pushbutton	Nickel-plated brass
Sealant	NBR
Spring	Stainless steel
Valve body	Aluminium

## Variants

<i>Article number</i>	<i>Connection</i>	<i>Price</i>
106413	Plug-in connector Ø 4 mm on side	37,40 € / Stk
106414	M5 female thread on side	36,69 € / Stk

## More Pictures

