


Datasheet for: 141526

Quick-connect coupling I.D. 7.8, Steel, Rigid, Hose 8x6

Quick-connect coupling I.D. 7.8, Steel, Rigid, Hose connection 8x6, Operating pressure - 35 bar, Temp. -20° C to 100 °C . Single-sided blocking, high quality and robust quick connect coupling for high flow values. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling. These quick disconnect couplings are not suitable for direct attachment to pulsating tools. We recommend using our vibration dampers, according to ISO 6150 § 7.1. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, workshops, automotive, mining.



Type number	244.41-E
Article number	141526
EAN/barcode	 4047322568210
Your price	17,91 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Ball	Stainless steel
Connection	Hose connection 8x6
DN	7.8
Flow rate	2000 l/min (air)
Flow rate measurement	at 6 bar and $\Delta_p = 0.5$ bar
Housing	Galvanised steel
Length	143.0 mm
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Operating pressure	- 35 bar
Page No.	HK549
Page No. SK	SK031
Sealant	NBR
Sleeve	Galvanised steel

Spring
 Threaded piece
 Valve
 Version
 a/f

Stainless steel
 Galvanised steel
 Die-cast zinc (zamac)
 Rigid
 19 mm

Variants

<i>Article number</i>	<i>Connection</i>	<i>Price</i>
141526	Hose connection 8x6	17,91 € / Stk
141528	Hose connection 12x9	17,91 € / Stk
141527	Hose connection 10x8	17,91 € / Stk

More Pictures

