

Datasheet for: 141527

Quick-connect coupling I.D. 7.8, Steel, Rigid, Hose 10x8


Quick-connect coupling I.D. 7.8, Steel, Rigid, Hose connection 10x8, Operating pressure - 35 bar, Temp. -20 °C to 100 °C . Single-sided blocking, high quality and robust quick connect coupling for high flow values. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling. These quick disconnect couplings are not suitable for direct attachment to pulsating tools. We recommend using our vibration dampers, according to ISO 6150 § 7.1. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, workshops, automotive, mining.

Type number	244.42-E
Article number	141527
EAN/barcode	 4047322568227
Your price	17,91 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Ball	Stainless steel
Connection	Hose connection 10x8
DN	7.8
Flow rate	2000 l/min (air)
Flow rate measurement	at 6 bar and $\Delta_p = 0.5$ bar
Housing	Galvanised steel
Length	160.0 mm
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Operating pressure	- 35 bar
Page No.	HK549
Page No. SK	SK031
Sealant	NBR
Sleeve	Galvanised steel

Spring
 Threaded piece
 Valve
 Version
 a/f

Stainless steel
 Galvanised steel
 Die-cast zinc (zamac)
 Rigid
 19 mm

Variants

<i>Article number</i>	<i>Connection</i>	<i>Price</i>
141527	Hose connection 10x8	17,91 € / Stk
141526	Hose connection 8x6	17,91 € / Stk
141528	Hose connection 12x9	17,91 € / Stk

More Pictures

