

Datasheet for: 107038


Compact pressure regulator, Quick connector for hose G 1/8 IT

Compact pressure regulator, Quick connector for hose G 1/8 IT, G 1/8, Control range 0-8 bar, Temp. 0°C to 70°C, nickel-plated brass. Piston pressure regulator with self-relieving design, hollow bolt and pivoting ring piece. The regulator is connected directly into the consumer (e.g. cylinder, handling equipment, etc.). The working pressure can thus be adapted to the specific application.

Type number	362.018-1/8
-------------	-------------

Article number	107038
----------------	--------

EAN/barcode	
-------------	--



4047322181594

Your price	27,60 € / Stk
------------	---------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Adjusting screw	Nickel-plated brass
B	56.0 mm
C	16.0 mm
Captive seals	Polyamide (glass fibre-reinforced)
For hose	G 1/8 female thread mm
Hollow bolt	Nickel-plated brass
Internal parts	Brass with a bare metal surface
Max. control range	8.0 bar
Max. input pressure	10 bar
Max. temperature range	70 °C
Min. control range	0.0 bar
Page No.	HK505
Pivoting arm	Nickel-plated brass
Sealant	NBR
Thread	G 1/8
a/f	15 mm

Variants

Article number	Thread	For hose	a/f	Price
107038	G 1/8	G 1/8 female thread mm	15 mm	27,60 € / Stk
107039	G 1/8	5 / 3 mm	15 mm	27,60 € / Stk
107040	G 1/8	6 / 4 mm	15 mm	27,60 € / Stk
107041	G 1/8	8 / 6 mm	15 mm	27,60 € / Stk
107042	G 1/4	6 / 4 mm	17 mm	27,60 € / Stk
107043	G 1/4	8 / 6 mm	17 mm	27,60 € / Stk
107044	G 1/4	10 / 8 mm	17 mm	27,60 € / Stk

More Pictures

