

## Datasheet for: 100955


**Filter »Standard«, Polycarbonate container, 5  $\mu$ m, Size 1, G 3/8**

 Filter »Standard« with polycarbonate container, 5  $\mu$ m, Size 1, G 3/8, Input pressure max. 16 bar, Med. / ambient temp. max. 60 °C . Centrifugal separators with a sintered filter element.

Type number	640.126 K-HA
Article number	100955
EAN/barcode	 4047322342179
Your price	24,45 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	48.0 mm
Bowl	Polycarbonate container
C	14.0 mm
Condensate drain	Semi-automatic
D	131.6 mm
DN	6.0
Filter rating	5.0 $\mu$ m
Flow rate	800 l/min
Flow rate measurement	At $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
H	38.0 mm
Housing	Die-cast zinc, painted silver
Max. ambient temperature	60 °C
Max. input pressure	16 bar
Max. medium temperature	60 °C
Page No.	HK125
Series	Standard
Size	1
Thread	G 3/8

## Variants

Article number	Thread	Filter rating	Flow rate	Size	DN	Price
100955	G 3/8	5.0 $\mu\text{m}$	800 l/min	1	6.0	24,45 € / Stk
100961	G 1 1/2	40.0 $\mu\text{m}$	12500 l/min	4	45.0	191,83 € / Stk
100954	G 1/4	5.0 $\mu\text{m}$	800 l/min	1	6.0	24,45 € / Stk
100959	G 1	5.0 $\mu\text{m}$	4000 l/min	3	25.0	103,58 € / Stk
100960	G 1 1/4	40.0 $\mu\text{m}$	12500 l/min	4	40.0	231,35 € / Stk
100962	G 2	60.0 $\mu\text{m}$	30000 l/min	5	55.0	549,33 € / Stk
100956	G 3/8	40.0 $\mu\text{m}$	3100 l/min	2	10.0	44,99 € / Stk
100957	G 1/2	5.0 $\mu\text{m}$	4000 l/min	3	15.0	44,99 € / Stk
100958	G 3/4	5.0 $\mu\text{m}$	4000 l/min	3	20.0	104,60 € / Stk

## More Pictures

